

ALTMANN ADT Mini

ON-POWER DEHYDRATION OF TRANSFORMERS



Installation of ADT Mini

The presence of moisture in the transformer, to whatever degree, actually harms the insulation which will be permanently damaged. Drying methods can substantially reduce that deterioration.

The **ADTmini** is intended for mobile and preventative use on transformers with more than 2 - 2.5% water content in the cellulose and with particle contamination.

The **quick restoration of safe dielectric conditions, life-extending features and remote control** also forms part of this concept. The system is especially suitable for drying of transformers situated in narrow, hardly accessible spaces.

Main features

- ❑ **Easy and safe installation and commissioning: all procedures are computer controlled to avoid any human lapses and errors**
- ❑ **No disconnection of the transformer under treatment, normally not even during installation of dehydrator (Plug & Play design)**
- ❑ **No air venting after installation: hydraulical interconnections to a transformer oil filling are set under vacuum and subsequently rinsed by oil**
- ❑ **Moisture and particles content can be reduced to the level of a new transformer**
- ❑ **Quick restoration of dielectric strength of oil**
- ❑ **No impact on the insulating oil properties and DGA**

- ❑ Direct check of dehydration efficiency based on amount of removed water: calculated as the product of difference input-output water content in oil (2 x humidity sensors) x precise volumetric reading of oil throughflow
- ❑ Easy and safely replacement of adsorbent cartridges and filters without a potential oil spill: the oil is removed before replacement and forced back to the oil filling of transformer
- ❑ Easy control of function by SMS via your handy
- ❑ Remote monitoring & control of drying process: all relevant data are recorded and displayed (printed) as easy comprehensive diagrams
- ❑ Calculation of actual value of dielectric strength (Ud-value) of oil during the whole dehydration
- ❑ Easy verification of simulated Ud-values by lab reading(s) by means of Verification diagram
- ❑ DOG (Dynamic Overdrying Guard) procedure inhibits the overdrying of hard insulants



Internal layout of main components (open doors)

References:

1. RWE Power
2. BASF
3. Voest Alpine
4. CEZ

For more details See please www.ars-altmann.com / Product Range

Contact
Hr. Altmann
Hr. Henghuber

Telephone
+ 420 379 738 778
+ 49 8727 7180

Handy
+420 602 362 157
+ 49 171 547 5391

e-mail
altmann@iol.cz
Ahenghuber@t-online.de

Specification:

Power supply voltage	1 phase 230 VAC (or on demand)
Power supply frequency	50 (60) Hz
Power consumption:	200 W
Oil throughput	7.5 m ³ per day maximum
Outlet water content	2 ppm nominal , 1 ppm minimum
Outlet filtering grade	1 µm (or on demand)
Absorption capacity(maximum)	2.6 kg of water
Installation options	mobile unit / permanently installed
Weight	
Mobile unit	
Dry weight (without oil)	152 kg
Operating weight (oil filled)	162 kg
Permanent installation	
Dry weight (without oil)	126 kg
Operating weight (oil filled)	136 kg
Dimensions	
Mobile version (cart)	750 x 650 1370 (mm)
Permanent installation	700 x 390 x 1260 (mm)
Hydraulical connection	2 x flexible 1/2" hose
Communication:	On request: Faxmodem,GSM modem, Internet modem, LAN link, SMS